

eTEC Floor Graphic Laminating Film R9

Product Description

A high-grade, structured, special PVC film with UV protection for the surface protection of floor advertising and Pop-Up displays. The structured surface eliminates blocking of the Pop-Up display when un-rolling and prevents scratches. Complies with the anti-slip specification DIN 51130 (R9). B1 Fire-rated DIN 4102 (German Fire Prevention Norm, Class B1)

Key Features

- 100 µm, transparent PVC-film
- One side siliconised surface-coated paper white release liner 63 g/m
- Pure polyacrylic, permanent, transparent adhesive
- Adhesive weight 30 g/m²
- Total Thickness 0.12 m
- B1 fire rated DIN 4102

Additional Information

Adhesion on steel: (after 24 h) 11 N/25mm AFERA 5001

Dimensional Stability: MD < -3% FTM 14

Dimensional Stability: CD < 1.5% FTM 14

Flammability: B1 DIN 4102

Application temperature: min. +8°C

End-Use Temperature range: from -40°C to +80°C

Shelf life: 2 years (see application information)

Durability: 3 months floor graphic (indoor applications)

The estimated durability is based on accelerated ageing tests and refers to a vertical exposure under middle European climates. The durability of the product depends on the substrate's preparation, the atmospheric conditions and the environmental influence. Exposure to extreme conditions (tropical climate, high humidity, high UV-light exposure or polluted areas) can decrease the durability in a dramatically way.

All values and information issues are approximate and should only be used as a guideline. Products should be tested by the end user for absolute suitability with the substrates and environments upon which it is intended to be used. Premier Paper cannot be held responsible for any damage to printing and finishing equipment or surfaces to which products are applied.