

eTEC Polymeric White Gloss Vinyl Perm Grey Adhesive

Product Description

High-quality, REACH and RoHS conform polymeric PVC film, suitable for colour intensive and brilliant prints for long-term advertisement both indoor and outdoor. Conformable Polymeric film suitable for use in curved surfaces and long-term outdoor prints. High adhesion to a wide variety of substrates including varying plastics, foamex, glass and aluminum. Excellent printing performance on a wide variety of solvent, eco-solvent, latex and UV digital print machines. Especially with a grey permanent adhesive for a high opacity.

Key Features

- 80 µm white glossy PVC film
- PE coated 140 g/m² white release paper
- Pure polyacrylic, permanent, grey adhesive
- Total Thickness 0.1 mm
- Adhesive weight 20 g/m
- B1 Fire Rated DIN 4102

Printability

Solvent, Eco Solvent, Latex & UV

Additional Information

Adhesion on steel: (after 20 min.) 8 N/25mm AFERA 5001

Adhesion on steel: (after 24 h) 16 N/25mm AFERA 5001

Dimensional Stability: MD < -3% FTM 14

Dimensional Stability: CD < -0% FTM 14

Flammability: B1 DIN 4102

Application temperature: min. +10°C

End-Use Temperature range: from -40°C to +80°C

Shelf life: 2 years (see application information)

Durability: 7 years

The estimated durability is based on accelerated ageing tests and refers to a vertical exposure under middle European climates. The durability of the product depends on the substrate's preparation, the atmospheric conditions and the environmental influence. Exposure to extreme conditions (tropical climate, high humidity, high UV-light exposure or polluted areas) can decrease the durability in a dramatically way

All values and information issues are approximate and should only be used as a guideline. Products should be tested by the end user for absolute suitability with the substrates and environments upon which it is intended to be used. Premier Paper cannot be held responsible for any damage to printing and finishing equipment or surfaces to which products are applied.