

HT Ultra

High Tack Ultra

EXCELLENT PRINTING SURFACE

HT ultra is a 4 mil (100µ) white monomeric self-adhesive PVC film with a high tack clear permanent adhesive that is protected by a 135gsm, 1 side siliconised white clay coated kraft liner. HT Ultra was designed for applications requiring a strong initial grab and subsequent bond on a variety of different surfaces including steel, glass, plastic, wood, and more.

- IDEAL FOR PERMANENT APPLICATIONS SUCH AS MACHINERY LABELS AND EQUIPMENT STICKERS.
- PROVIDES A STRONG BOND TO MOST FLAT SURFACES.
- SUITABLE FOR INDOOR & OUTDOOR USE

100
micron

White
Monomeric
PVC

Matte or
Gloss



(Eco)Solvent
Latex
UV



Clear High-Tack
Acrylic Adhesive



Widths up to 1370mm



3 YEARS DURABILITY
INTERIOR & EXTERIOR



APPLICATIONS

Machinery Labels
General Signage
Decals & Stickers



DRYTAC[®]

ADHESIVE SCIENCE

www.drytac.com

HT Ultra

TECHNICAL SPECIFICATION

HT ultra is a 4 mil (100µ) white monomeric self-adhesive PVC film with a high tack clear permanent adhesive that is protected by a 135gsm, 1 side siliconised white clay coated kraft liner. HT Ultra was designed for applications requiring a strong initial grab and subsequent bond on a variety of different surfaces including steel, glass, plastic, wood, and more.

- IDEAL FOR PERMANENT APPLICATIONS SUCH AS MACHINERY LABELS AND EQUIPMENT STICKERS.
- PROVIDES A STRONG BOND TO MOST FLAT SURFACES.
- SUITABLE FOR INDOOR & OUTDOOR USE

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

PRODUCT STRUCTURE

Film	White Matte or Gloss Monomeric PVC
Adhesive	High Tack Clear Permanent Acrylic (Pressure Sensitive)
Release Liner	135gsm 1 Side Siliconised White Clay Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	4 mil (100µ) 4.2 mil (105µ)
Adhesive Layer	1 mil (25µ) (105µ)
Outdoor Durability	3 Years (Unprinted)
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)
Shelf Life	2 years
Storage Conditions	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity

OVERLAMINATE RECOMMENDATIONS

When using HT Ultra, an overlamine can be used for maximum life expectancy. Products recommended for use with HT Ultra are Drytac's Interlam™ products.

DRYTAC[®]
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013