

Polar®

Chrome

Polar® Chrome is a 75 micron printable reflective silver PET film with a clear permanent acrylic adhesive. Create engaging displays and signage with this bold reflective film. Polar® Chrome is ideal for indoor/short-term outdoor signage, billboards and exhibitions hall displays, POS displays, bus or subway advertisements.

- IDEAL FOR PROMOTIONAL GRAPHICS OR DECALS
- SUITABLE FOR INDOOR OR SHORT-TERM GRAPHICS
- EYE-CATCHING REFLECTIVE FACE FILM

Product Code: PCH

75 Silver Reflective
micron PET

■
Satin



(Eco) Solvent
Latex
UV



Clear
Permanent
Adhesive



Widths up to 60 in

YEARS DURABILITY
3

INTERIOR

YEARS DURABILITY
2

EXTERIOR*

STRIKING REFLECTIVE FILM



APPLICATIONS

SIGNAGE

BILLBOARDS

EXHIBITION HALLS

RETAIL & POP DISPLAY



DRYTAC®

ADHESIVE SCIENCE

www.drytac.com

Polar®

Chrome

Polar® Chrome is a 3 mil (75µ) premium, silver satin PET film with a clear permanent pressure sensitive acrylic adhesive that is protected by a siliconised 1 side PET liner. Polar® Chrome provides a superb printing surface for eye-catching color graphics, interior or exterior.

- EYE-CATCHING REFLECTIVE FACE FILM
- CAN BE USED TO CREATE ULTRA-REFLECTIVE LABELS
- IDEAL FOR POSTERS, BILLBOARDS, EXHIBITION HALL DISPLAYS, TRADE SHOW, POP DISPLAYS AND BUS OR SUBWAY ADVERTISEMENTS

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2019 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Silver Satin PET
Adhesive	Clear Permanent Acrylic (Pressure Sensitive)
Release Liner	Siliconised 1 Side PET

PRODUCT CHARACTERISTICS

Film Thickness	3 mil (75µ) 4 mil (100µ)
Adhesive Layer	1 mil (25µ) (100µ)
*Outdoor Durability	2 Years (ink dependent - see warranty for details)
Application Temperature	>41°F (5°C)
Service Temperature Range	59°F to 86°F (15°C to 30°C)
Shelf Life	1 year
Storage Conditions	50°F to 77°F (10°C to 25°C); 20% Relative Humidity

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com