



GC2

PRODUCT INFORMATION

An impeccable, fully coated, hard sized folding boxboard with an uncoated cream reverse for a toothy feel. White Peak GC2 is an excellent choice for a wide variety of end uses and can be foiled, blocked, embossed and laminated.

This product is produced using ECF pulp from FSC® certified sources, ISEGA certified for direct food contact and is fully recyclable. ISO 9001 and ISO 14001 approved supplier.

SUGGESTED USES ● Point of sale displays ● cartons for cosmetics
● health care & pharmaceuticals ● food packaging ● Frozen & chilled food packaging

PROCESS SUITABILITY

White peak GC2 is ideal for litho, gravure letterpress, flexo and screen printing. It's also suitable for UV and litho varnishing, emulsion coating, foil and film laminating, embossing and foil blocking. Not suitable for reverse printing.

STOCK SCHEDULE

	Micron	356	406	432	470	500	533	610	690
	gsm	215	235	250	260	275	295	325	370
450mm x 640mm		●	●	●	●	●	●	●	
520mm x 720mm		●	●	●	●	●	●	●	
550mm x 750mm						●			
600mm x 800mm					●	●		●	
640mm x 900mm			●	●	●	●	●	●	●
720mm x 1020mm		●	●	●	●	●	●	●	●
720mm x 950mm			●		●	●	●	●	
950mm x 720mm					●			●	
1020mm x 720mm			●	●		●			●

● = Available from stock for next-day delivery



SPECIFICATION

Technical Information									
Grammage (gsm)		215	235	250	260	275	295	325	370
Thickness (mic)		356	406	432	470	500	533	610	690
Gloss (Hunter 75°) (%)		40	40	40	40	40	40	40	40
Stiffness (Taber 15°) (mNm)	MD	9.4	12.3	15.4	19.8	24.1	29.1	37.4	51
	CD	4.5	6	7.4	9.5	11.3	14	18	23

CREDENTIALS



The CO₂ emissions from this product can be mitigated through the Carbon Capture® programme, directly supporting the work of the Woodland Trust.

The above information is given for general guidance only and is subject to change without notice.