

Self-Adhesive Machine Coated Matt (Digital)

FEDRIGONI

Product information

Machine Coated Matt is a 192mic self-adhesive sheet with a minimum of 40% selected recycled fibres. It is one of the whitest, triple-coated, ECF and FSC certified face materials on the market. The permanent adhesive benefits from special anti-bleeding properties and has excellent resistance to thermal shock. It is available with a single-side siliconised clay coated white kraft liner in a split back. It is a truly versatile product suitable for use across a wide range of applications.

Applications

Premium promotions and branding • Specialty food and beverage

Print and finishing

Dry Toner and HP Indigo® • Main cutting and die-cutting processes

Specification

FACE MATERIAL

Weight ISO 536 (gsm)		90 ± 3%
Thickness ISO 536 (mic)		79.2
Roughness ISO 8791-2 (ml/min)		40 ± 20%
Breaking load ISO 1924 (kN/m)	Long	3.7 ± 10%
	Cross	2.8 ± 10%

ADHESIVE

Adhesive type	Permanent	Removable
Tack (N/inch)	>9	
Min. cohesion (hours)	>9	0.5
Application temperature °C	+5	+5
Min. service temperature °C	-10	-10
Max. service temperature °C	+80	+80

LINER

Weight ISO 536 (gsm)		82
Thickness ISO 536 (mic)		85
Opacity ISO 2471 (%)		82 ± 2
Breaking load ISO 1924 (N/15mm)	Long	65
	Cross	35

Stock schedule

Size	Backing	
	Split	Solid
450 x 320mm Permanent	●	
450 x 320mm Removable	●	

● Ream wrapped

Credentials



The CO₂ emissions from this product can be mitigated through the Carbon Capture® programme, directly supporting the work of the Woodland Trust.

Approved for toy safety, European standard UNI EN 71.

This information is given for general guidance only and is subject to change without notice.