

Eska Black is a superior fully recyclable board which has been specially developed for use in the luxury packaging industry. Its superb strength and rigidity ensure that it lays flat and stays flat, while its deep black colour and excellent runnability deliver high-quality results for premium packaging applications.

Process suitability

Direct to substrate printing • Screen printing • Embossing • Debossing • Grooving • Punching • Drilling • Die cutting

Suggested uses

Luxury packaging • Rigid boxes • Retail POS displays

Specification				
Thickness (mic) ISO 534		1000	1500	1750
Grammage (gsm) ISO 536		715	1015	1190
Dynamic stiffness (mNm) ISO 5629	MD	335	970	1910
	CD	220	615	1060
Bursting Strength (kPa) ISO 2759	Top	1200	1285	1890
	Bottom	1200	1315	1770
COBB60 (gsm/60sec) ISO 535	Max Top	50	50	50
	Max Bottom	50	50	50

Stock schedule			
mic	1000	1500	1750
gsm	715	1015	1190
750mm x 1050mm	●	●	●
880gsm/1250mic and 1370gsm/2000mic are available as mill makings.			

Credentials



The CO₂ emissions from this product can be mitigated through the Carbon Capture[®] programme, directly supporting the work of the Woodland Trust.

This information is given for general guidance only and is subject to change without notice.